

GLASS TAGS



FEATURES and SPECIFICATIONS:

Operating Frequency * - 134.2KHz
ISO 11784/11785 Standards Compliant
Read Only or Read/Write Versions

Size ** - Length 32 mm +/- 1mm
Dia 3.85mm +/- 0.1mm

Material *** – Bio-Grade Glass + Epoxy

Operating Temperature: -25 degC to +85 degC
Storage Temperature : -40 degC to +85 degC

Withstands Mechanical Vibrations up to 10g, 10-2000Hz, 3 axis, 2.5 hrs
Withstands Mechanical Shock up to 40g, half-sine, 18ms, 6 axis, 2000 times
Withstands Water Immersion as per IP 68

Read Distance varies for different tag sizes and depends on the User's reader antenna

* Glass Tags also available at 125 KHz
** Other Sizes available on request
*** Industrial grade glass tags also available

Syrma Technology reserves the right to change the product information, specification, features or data without any prior notice at any time. Syрма Technology does not take any responsibility for customer product/system design or performance when used with specifications not mentioned above.

Syrma Technology Pvt. Ltd.

Plot B27, Phase 2, Zone B, MEPZ Special Economic Zone, Tambaram, Chennai-600045, INDIA
Tel: +91 44 22628600 Fax: +91 44 22628612 Email: info@syrmatech.com URL: www.syrmatech.com